

LINKSYS®

A Division of Cisco Systems, Inc.

Gigabit Ethernet Switch with 24-port 10/100/1000 with 4 shared SFP slots and stacking

SGE2000 is optimized for maximizing the system availability with fully redundant stacking, redundant power options, and dual images for resilient firmware upgrades. The SGE2000 is able to secure the network through IEEE 802.1Q VLANs, IEEE 802.1X port authentication, Access Control Lists (ACL), DOS prevention, and MAC-based filtering. The enhanced QoS and traffic management features ensure clear and reliable voice and video communications

The SGE2000 Switch includes an intuitive, secure management interface enabling you to better utilize the comprehensive feature-set of the SGE2000, resulting in a better optimized, more secure network.

Linksys Business Series SFE and SGE Stackable Switch products are Linksys One Ready. That means they include the necessary firmware to be seamlessly integrated into a Linksys One data or data/voice network. Once connected, a Linksys One Service Router will discover the SFE/SGE device, automatically configure it and make it available to other users on the network. Linksys One technology is automatic and self-configuring. When other Linksys One peripherals are connected to a Linksys One Ready Ethernet Switch's ports, small businesses are ready to communicate in a matter of minutes.

Fully resilient stacking provides optimized growth with simplified management

Granular QoS options makes solution ideal for improved application experience

Maximum security and control of traffic with policing, shaping, ACLs, and QoS

Linksys One Ready - simple, automated installation with Linksys One Services Routers present



PRODUCT DATA

24-Port 10/100/1000 Gigabit Switch

BUSINESS SERIES



Model: SGE2000



Features

- 24 10/100/1000 Ethernet ports
- 4 SFP slots (shared with 4 copper ports) for Fiber Gigabit Ethernet expansion
- Dual images for resilient firmware upgrades
- Up to 48 Gbps, non-blocking, Store-and-Forward switching capacity
- Simplified QoS management using 802.1p, Diffserv or ToS traffic prioritization specifications
- Power redundancy when used with Linksys Business Series Redundant Power Supply unit (RPS1000)
- Fully resilient stacking provides optimized growth with simplified management
- Access Control Lists (ACL) for granular security and QoS implementation
- Management enables configuration and monitoring from a standard web browser
- Secure remote management of the switch via SSH and SSL encryption
- 802.1Q based VLANs enable segmentation of networks for improved performance and security
- Private VLAN Edge for simplified network isolation for guests connections or autonomous networks

PRODUCT DATA

BUSINESS SERIES

24-Port 10/100/1000 Gigabit Switch

Specifications

Model	SGE2000 - 24-Port 10/100/1000 Gigabit Switch
Ports	24 RJ-45 Connectors for 10BASE-T/100BASE-TX/1000BASE-T with 4 Shared Gigabit SFP Slots Console Port Auto MDI/MDI-X Autonegotiate/Manual Setting RPS Port for Connecting to Redundant Power Supply Unit Reset Button
Buttons	
Cabling Type	UTP CAT 5 or Better for 10BASE-T/100BASE-TX, UTP CAT 5e or Better for 1000BASE-T
LEDs	PWR, Fan, Link/Act, Speed, RPS, Master, Stack ID 1 - 8

Performance

Switching Capacity	Up to 48 Gbps, Non-Blocking
Forwarding Rate (Based on 64-Byte Packets)	Up to 35.7Mpps

Stacking

Stack Operation	Up to 8 Units in a Stack (192 Ports) Hot Insertion and Removal Ring and Chain Stacking Options Master and Backup Master for Resilient Stack Control Auto-Numbering or Manual Configuration of Units in Stack
-----------------	--

Layer 2

MAC Table Size	8K
Number of VLANs	256 Active VLANs (4096 Range)
VLAN	Port-Based and 802.1Q Tag-Based VLANs Protocol-Based VLAN Management VLAN Private VLAN Edge (PVE) GVRP
HOL Blocking	Head of Line Blocking Prevention

Layer 3

Layer 3 Options	Static Routing CIDR (Classless Interdomain Routing) 128 Static Routes IPv4 Forwarding in Silicon - Wirespeed Forwarding of Layer 3 Traffic
-----------------	--

Management

Web User Interface	Built-In Web UI for Easy Browser-Based Configuration (HTTP/HTTPS)
SNMP	SNMP Version 1, 2c, 3 with Support for Traps
SNMP MIBs	RFC1213 MIB-2, RFC2863 Interface MIB, RFC2665 Ether-like MIB, RFC1493 Bridge MIB, RFC2674 Extended Bridge MIB (P-bridge, Q-bridge), RFC2819 RMON MIB (groups 1,2,3,9 only), RFC2737 Entity MIB, RFC3621 Power Ethernet MIB, RFC 2618 RADIUS Client MIB RFC 1215 Traps
RMON	Embedded Remote Monitoring (RMON) Software Agent Supports Four RMON Groups (History, Statistics, Alarms, and Events) for Enhanced Traffic Management, Monitoring, and Analysis
Firmware Upgrade	Web Browser Upgrade (HTTP) and TFTP Dual Images for Resilient Firmware Upgrades
Port Mirroring	Traffic on a Port can be Mirrored to Another Port for Analysis with a Network Analyzer or RMON Probe

- Automatic configuration of VLANs across multiple switches through GVRP/GARP
- User/Network port level security via 802.1x authentication and MAC-based filtering
- Increased bandwidth and added link redundancy with Link Aggregation
- Enhanced rate limiting capabilities, including back pressure, multicast, and broadcast flood control
- Port mirroring for non-invasive monitoring of switch traffic
- Mini jumbo frame support (1600 bytes)
- SNMP v1, v2c, v3 and RMON support
- Fully rack-mountable using the included rack-mounting hardware
- Linksys One Ready - Simple, one-step automated installation and initial configuration

PRODUCT DATA

BUSINESS SERIES

Other Management

Traceroute
Single IP Management
Secure Socket Layer (SSL) security for Web UI
Secure Shell (SSH)
RADIUS
Port Mirroring
TFTP Upgrade
DHCP Client
BootP
SNTP
Xmodem Upgrade
Cable Diagnostics
PING
Syslog
Telnet Client (SSH Secure Support)

Security

IEEE 802.1x

802.1x - RADIUS Authentication. MD5 Hash
Guest VLAN
Single/Multiple Host Mode

Access Control

ACLs - Drop or Rate Limit Based on:
Source and Destination MAC-Based
Source and Destination IP Address
Protocol
Port
VLAN
DSCP/IP Precedence
TCP/UDP Source and Destination Ports
802.1p Priority
Ethernet Type
ICMP Packets
IGMP Packets
Up to 1018 Rules

Availability

Link Aggregation

Link Aggregation using IEEE 802.3ad LACP
Up to 8 Ports in up to 8 Groups

Storm Control
DOS Prevention
Spanning Tree

Broadcast and Multicast Storm Protection
DOS Attack Prevention

IGMP Snooping

IEEE 802.1D Spanning Tree, IEEE 802.1w Rapid Spanning Tree, IEEE 802.1s Multiple Spanning Tree, Fast Linkover

Power Redundancy

IGMP (v1/v2) Snooping Limits Bandwidth-Intensive Video Traffic to only the Requestors. Supports 256 Multicast Groups
Connection to RPSU for Power Redundancy

QoS

Priority levels
Scheduling
Class of Service

4 Hardware Queues
Priority Queuing and Weighted Round Robin (WRR)
Port-Based
802.1p VLAN Priority Based
IPv4 IP Precedence/TOS/DSCP Based
Diffserv
Classification and Remarking ACLs
Ingress Policer
Egress Rate Control

Rate Limiting

Standards

802.3 10BASE-T Ethernet, 802.3u 100BASE-TX Fast Ethernet, 802.3ab 1000BASE-T Gigabit Ethernet, 802.3z Gigabit Ethernet, 802.3x Flow Control, 802.3ad LACP, 802.1d STP, 802.1Q/p VLAN, 802.1w Rapid STP, 802.1s Multiple STP, 802.1x Port Access Authentication

Environmental

Dimensions W x H x D	17.32" x 14.70" x 1.73" (440 x 375 x 44 mm)
Unit Weight	14.09 lb (6.39 kg)
Certification	UL (UL 60950), CSA (CSA 22.2), CE mark, FCC Part 15 (CFR 47) Class A
Operating Temp.	32 to 104°F (0 to 40°C)
Storage Temp.	-4 to 158°F (-20 to 70°C)
Operating Humidity	10 to 90% Relative Humidity, Noncondensing
Storage Humidity	10 to 95% Relative Humidity, Noncondensing
Number of Fans	2
Acoustic Noise	55dB Max.
Power	100-240VAC, 50-60Hz, Internal, Universal; Also Equipped with Redundant Power Supply Connector for External Power Supply 48VDC
Power Consumption	12V@7.5A (90W)

Package Contents

- SGE2000 - 24-Port 10/100/1000 Gigabit Switch
- Console Cable
- AC Power Cord
- Rack-Mount Kit
- Quick Installation Guide

Minimum Requirements

- Web Browser - Mozilla Firefox 1.5 or Later, IE 5.5 or Later, Netscape 7.01 or Later
- Cat5 Ethernet Network Cable
- TCP/IP Protocol Installed on Each Computer Within the Network
- Network Adapter Installed in Each Computer
- Network Operating System
- Provider Support for CPE Software Version 1.2 or Higher

Linksys
A Division of Cisco Systems, Inc.
121 Theory
Irvine, CA 92617 USA

E-mail: sales@linksys.com
support@linksys.com
Web: <http://www.linksys.com>

Linksys products are available in more than 50 countries, supported by 12 Linksys Regional Offices throughout the world. For a complete list of local Linksys Sales and Technical Support contacts, visit our Worldwide Web Site at www.linksys.com.

PRODUCT DATA

BUSINESS SERIES