



ARUBA 2530 24G SWITCH (J9776A)

Fixed Port L2 Managed Ethernet Switches



WHAT'S NEW

- Cost-effective, reliable and secure Aruba Layer 2 switch series for a better mobile-first experience.
- ACLs, EEE, traffic prioritization.
- 8-, 24-, and 48-port Gigabit or Fast Ethernet models.
- PoE+ models for voice, video and wireless.
- Supports Aruba ClearPass Policy Manager, AirWave and Central.
- Simple deployment with zero touch provisioning (ZTP).

OVERVIEW

The Aruba 2530 Switch Series provides security, reliability, and ease of use for enterprise edge, branch office, and SMB deployments. Fully managed switches deliver Layer 2 capabilities with optional PoE+, enhanced access security, traffic prioritization, sFlow, IPv6 host support, and power savings with Energy Efficient Ethernet. The Aruba 2530 Switch Series is easy to use and deploy, and delivers consistent wired/wireless user experience with unified security and management tools such as Aruba ClearPass Policy Manager, Aruba AirWave and cloud-based Aruba Central.

FEATURES

Cost-Effective, Reliable and Secure Access Layer Switches

The Aruba 2530 Switch Series provides security, reliability, and ease of use for enterprise edge, branch office, and SMB deployments.

Fully managed switches deliver full Layer 2 capabilities with optional PoE+, enhanced access security, traffic prioritization, sFlow, and IPv6 host support.

Right size deployment with choice of 8-, 24-, and 48-port models available with Gigabit or Fast Ethernet ports, and optional PoE+.

Power savings with fanless models, Energy Efficient Ethernet (IEEE 802.3az), and ability to disable LEDs and enable port low power mode.

Delivers consistent wired/wireless user experience with unified security and management tools such as ClearPass Policy Manager, AirWave and cloud-based Central. Provides optimal configuration automatically when connected to Aruba APs for PoE priority, VLAN configuration, and rogue AP containment.

Security and Quality of Service (QoS)

The Aruba 2530 Switch Series supports flexible authentication methods including Local MAC, 802.1X, and MAC and Web for greater policy-driven application security.

Advanced denial of service (DOS) protection, such as DHCP Protection, Dynamic ARP protection, and Dynamic IP lockdown, enhance security. Flexible traffic controls include ACLs and QoS.

Traffic prioritization with IEEE 802.1p allows real-time traffic classification with support for eight priority levels mapped to either two or four queues using weighted deficit round robin (WDRR) or strict priority (SP).

Defend your IPv6 network with DHCPv6 Protection.

Simple Deployment and Management

The Aruba 2530 Switch Series supports a choice of management interfaces with Web GUI, command-line interface (CLI), and SNMP with either console or micro USB ports.

Quiet operation with fanless and variable speed fan models.

Flexible deployment with wall, table, and rack mounting options.

Zero touch provisioning (ZTP) provides quick and painless deployment at locations with few or no technical resources.

Single View of the Network

The Aruba 2530 Switch Series supports Aruba ClearPass Policy Manager for unified and consistent policy between wired and wireless users and simplifies implementation and management of guest login, user onboarding, network access, security, QoS, and other network policies.

Supports Aruba AirWave network management software to provide common platform for zero touch provisioning management, and monitoring for wired and wireless network devices.

RMON and sFlow provide advanced monitoring and reporting capabilities for statistics, history, alarms, and events.

Aruba Central cloud-based management platform offers simple, secure, and cost



effective way to manage switches.

Supports both cloud-based Central and on-premise AirWave with the same hardware ensuring change of management platform without ripping and replacing switching infrastructure.

Technical specifications

Aruba 2530 24G Switch

Product Number (SKU)	J9776A
Differentiator	Cost-effective 28-port fully managed Gigabit Layer 2 switch. This model has 24x 10/100/1000 ports and four Gigabit SFP ports.
Ports	(24) RJ-45 autosensing 10/100/1000 ports (4) fixed Gigabit Ethernet SFP ports
Memory and processor	ARM9E @ 800 MHz 128 MB flash Packet buffer size: 1.5 MB dynamically allocated 256 MB DDR3 DIMM
Latency	100 Mb Latency: < 7.4 µs 1000 Mb Latency: < 2.3 µs
Throughput	up to 41.6 Mpps
Switching capacity	56 Gbps
Stacking capabilities	Virtual 16 switches
Management features	Aruba Central and Aruba AirWave Network Management IMC—Intelligent Management Center command-line interface Web browser configuration menu out-of-band management (serial RS-232C or Micro USB) IEEE 802.3 Ethernet MIB Repeater MIB Ethernet Interface MIB AirWave Network Management
Input voltage	100 - 127 / 200 - 240 VAC, rated
Operating humidity range	15 to 95% @ 104°F (40°C) (noncondensing)
Power Consumption	48 W (maximum)
Heat dissipation	164 BTU/hr (173.02 kJ/hr)
Minimum dimensions (H x W x D)	44.3 x 25.4 x 4.45 cm
Weight	2.77 kg



For additional technical information, available models and options, please reference the [QuickSpecs](#)

HPE POINTNEXT

Access expertise at every step of your IT journey with [HPE Pointnext Services](#). [Advisory Services](#) focuses on your business outcomes and goals, to design your transformation and build a roadmap tuned to your unique challenges. Our [Professional](#) and [Operational Services](#) help speed up time-to-production and keep your IT stable and reliable.

Operational Services from HPE Pointnext Services

- [HPE Datacenter Care](#) helps modernize and simplify IT operations. Partner with an assigned account team, access technical expertise, an enhanced call experience gives you priority access, choose hardware and software support, implement proactive monitoring to help stay ahead of issues, and access HPE IT best practices and IP.
- [HPE Proactive Care](#) offers an enhanced call experience and helps reduce problems with personalized proactive reports and advice. This also includes collaborative software support for Independent Software Vendors (ISVs), (Red Hat, VMWare, Microsoft, etc.). [Read more](#)
- [HPE Foundation Care](#) helps when there is a problem and has a choice of response levels. Collaborative software support is included and provides troubleshooting help for ISVs running on your server. [Read more](#).

Other related services

Defective Media Retention is optional and applies only to Disk or eligible SSD/Flash Drives replaced by HPE due to malfunction.

[HPE Service Credits](#) offers a menu of technical services, access additional resources, and specialist skills.

[HPE Education Services](#) provides comprehensive training designed to expand the skills of your IT staff and keep them up to speed with the latest technologies.

Consult your HPE Sales Representative or Authorized Channel Partner of choice for any additional questions and support options.

HPE GREENLAKE

[HPE Greenlake](#) is HPE's market-leading IT as-a-Service offering that brings the cloud experience to apps and data everywhere – data centers, multi-clouds, and edges – with one unified operating model. HPE GreenLake delivers public cloud services and infrastructure for workloads on premises, fully managed in a pay per use model.

If you are looking for more services, like **IT financing solutions**, please [explore them here](#).

Make the right purchase decision.
Contact our presales specialists.

[Find a partner](#)



Chat now (sales)



Call now



Share now



Get updates



**Hewlett Packard
Enterprise**

© Copyright 2020 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Parts and Materials: HPE will provide HPE-supported replacement parts and materials required to maintain the covered hardware.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

Image may differ from the actual product
[PSN5333811ILEN](#), June 06, 2020.